ARTIFACT SHEET

Enter artifact number below. Artifact number is application number + artifact type code (see list below) + sequential letter (A, B, C.). The first artifact folder for an artifact type receives the letter A, the second B, etc Examples: 59123456PA, 59123456PB, 59123456ZA, 59123456ZB [Indicate quantity of a single type of artifact received but not scanned. Create artifact number for each Artifact Type.]			
individual artifact folder/box and artifact number for each Artifact Type.			
CD(s) containing: computer program listing Doc Code: Computer pages of specification Artifact Type Code: P			
and/or sequence listing and/or table			
Doc Code: Artifact Artifact Type Code: S			
content unspecified or combined Doc Code: Artifact Artifact Type Code: U			
Stapled Set(s) Color Documents or B/W Photographs Doc Code: Artifact Type Code: C			
Microfilm(s) Doc Code: Artifact Type Code: F			
Video tape(s) Doc Code: Artifact Type Code: V			
Model(s) Doc Code: Artifact Type Code: M			
Bound Document(s) Doc Code: Artifact Type Code: B			
Confidential Information Disclosure Statement or Other Documents marked Proprietary, Trade Secrets, Subject to Protective Order, Material Submitted under MPEP 724.02, etc. Doc Code: Artifact Artifact Type Code X			
Other, description: Doc Code: Artifact Type Code: Z			

The United States of America



The Commissioner of Patents and Trademarks

Has received an application for a patent for a new and useful invention. The title and description of the invention are enclosed. The requirements of law have been complied with, and it has been determined that a patent on the invention shall be granted under the law.

Therefore, this

United States Patent

Grants to the person(s) having title to this patent the right to exclude others from making, using, offering for sale, or selling the invention throughout the United States of America or importing the invention into the United States of America for the term set forth below, subject to the payment of maintenance fees as provided by law.

If this application was filed prior to June 8, 1995, the term of this patent is the longer of seventeen years from the date of grant of this patent or twenty years from the earliest effective U.S. filing date of the application, subject to any statutory extension.

If this application was filed on or after June 8, 1995, the term of this patent is twenty years from the U.S. filing date, subject to any statutory extension. If the application contains a specific reference to an earlier filed application or applications under 35 U.S.C. 120, 121 or 365(c), the term of the patent is twenty years from the date on which the earliest application was filed, subject to any statutory extension.

Buce Tehran

Melvinia Hary



US005764724A

United States Patent [19]

Ohlson

[11] Patent Number:

5,764,724

[45] Date of Patent:

Jun. 9, 1998

[54] METHOD OF MAKING X-RAY
PHOTOGRAPHS OR EXPOSURES OR
OTHER TYPE OF RADIATION SENSORING,
SUCH AS ELECTRONIC IMAGE STORAGE,
AND A PATIENT TABLE HAVING A
RECEPTOR UNIT FOR SUCH
PHOTOGRAPHY, EXPOSURE OR IMAGE
STORAGE

[75] Inventor: Carl-Eric Ohlson, Stockholm, Sweden

[73] Assignee: AO Medical Products AB, Stockholm,

Sweden

[21] Appl. No.: 776,392

[22] PCT Filed: Jul. 26, 1995

[86] PCT No.: PCT/SE95/00887

§ 371 Date: Jan. 28, 1997

§ 102(e) Date: Jan. 28, 1997

[87] PCT Pub. No.: WO96/03077

PCT Pub. Date: Feb. 8, 1996

[30] Foreign Application Priority Data

378/175, 169, 170, 178, 179, 181, 208, 209, 187

[56] References Cited

U.S. PATENT DOCUMENTS

4,468,803	8/1984	Ronci	378/181
5,023,899	6/1991	Ohlson	378/177
5,157,707	10/1992	Ohlson	378/181

FOREIGN PATENT DOCUMENTS


463237 B 10/1990 Sweden .

Primary Examiner—Don Wong Attorney, Agent, or Firm—Sughrue, Mion, Zinn, Macpeak & Seas, PLLC

[57] ABSTRACT

A method of X-ray photography or a method of some other type of radiation sensoring, such as electronic image storage. employs the use of a receptor unit (2) which can be swung outwards and upwards from an initial position in or beneath a patient support table (1) about alternative pivot centers (11. 12) disposed in the region of respective side edges of the table to alternative positions for operating with a horizontal beam path. The receptor unit can be swung out about a vertical axis from these positions in which it is parallel with the longitudinal direction of the table to a position in which it is parallel with the longitudinal direction of the table to a position in which the unit is perpendicular to the longitudinal axis of the table, to enable pictures to be taken of a patient seated in a wheelchair, for instance. The invention also relates to a patient support table (1) provided with a receptor unit (2) of this kind.

19 Claims, 9 Drawing Sheets



tenance fees ears and six reafter upon the mainteapplicable date the fee of the end of